



Silicone Coolant Hose

Inside Diameter	Outside Diameter	Wall Thickness	Working Pressure	Bursting Pressure	No. Of Ply	Coil Weight	Coil Length
13mm	22mm	4.5mm	9 Bar	27 Bar	3	7.3kg	20 Metre
16mm	25mm	4.5mm	8.33 Bar	25 Bar	3	8.6kg	20 Metre
19mm	28mm	4.5mm	7.17 Bar	19.5 Bar	3	9.5kg	20 Metre
22mm	31mm	4.5mm	6.5 Bar	17.4 Bar	3	10.9kg	20 Metre
25mm	34mm	4.5mm	5.8 Bar	16.5 Bar	3	12.2kg	20 Metre
28mm	37mm	4.5mm	5.5 Bar	16 Bar	3	12.3Kg	20 Metre
30mm	39mm	4.5mm	5.33 Bar	16 Bar	3	12.4kg	20 Metre
32mm	41mm	4.5mm	5.17 Bar	15.5 Bar	3	14.4kg	20 Metre
51mm	61mm	5mm	4.5 Bar	13.5 Bar	4	6kg	5 Metre

SKU - CSH

Operating Temperature
-50°C to +180°C

Peak Temperature
+250°C

Inner Layer Material
Silicone

Reinforcement
Multi Fabric Cord Layers

Outer Layer Material
Silicone

Standard
SAEJ20R3

Colour



View Product Online

Hoses UK

Unit 5 Holme Bank Mills
Station Road
Mirfield
West Yorkshire
WF14 8NA

Contact:

01924 496111
web@hosesuk.co.uk
hosesuk.co.uk

Hose Distribution. Simplified.