

Silicone Fuel & Oil Hose

Inside Diameter	Outside Diameter	Wall Thickness	Working Pressure	Bursting Pressure	Number Of Ply	Coil Weight	Coil Length
6mm	15mm	4.5mm	10 Bar	30 Bar	3	0.17kg	1 Metre
8mm	17mm	4.5mm	10 Bar	30 Bar	3	0.19kg	1 Metre
9.5mm	18.5mm	4.5mm	10 Bar	30 Bar	3	0.23kg	1 Metre
13mm	22mm	4.5mm	8.3Bar	27 Bar	3	0.26kg	1 Metre
16mm	25mm	4.5mm	7.1 Bar	25 Bar	3	0.30kg	1 Metre
19mm	28mm	4.5mm	6.5 Bar	19.5 Bar	3	0.31kg	1 Metre
22mm	31mm	4.5mm	5.8 Bar	17.4 Bar	3	0.37kg	1 Metre
25mm	34mm	4.5mm	5.5 Bar	16.5 Bar	3	0.37kg	1 Metre
28mm	37mm	4.5mm	5.3 Bar	16 Bar	3	0.41kg	1 Metre
30mm	39mm	4.5mm	5.3 Bar	16 Bar	3	0.41kg	1 Metre
32mm	41mm	4.5mm	5.1 Bar	15.5 Bar	3	0.50kg	1 Metre
35mm	44mm	4.5mm	5 Bar	15 Bar	3	0.54kg	1 Metre
38mm	47mm	4.5mm	5 Bar	15 Bar	3	0.60kg	1 Metre
40mm	49mm	4.5mm	4.8 Bar	14 Bar	3	0.69kg	1 Metre
45mm	54mm	4.5mm	4.6 Bar	14 Bar	3	0.71kg	1 Metre
48mm	57mm	4.5mm	4.5 Bar	13.5 Bar	3	0.77kg	1 Metre
51mm	62mm	5.5mm	4.5 Bar	13.5 Bar	4	0.94kg	1 Metre
54mm	65mm	5.5mm	4.3 Bar	13 Bar	4	0.99kg	1 Metre
57mm	68mm	5.5mm	4.3 Bar	13 Bar	4	1.01kg	1 Metre
60mm	71mm	5.5mm	4.1 Bar	12.5 Bar	4	1.04kg	1 Metre
63mm	74mm	5.5mm	4 Bar	12 Bar	4	1.21kg	1 Metre

SKU - FSL

Operating Temperature

-50°C to +250°C

Peak Temperature

+250°C

Inner Layer Material

Silicone

Reinforcement

Polyester Braid

Outer Layer Material

Silicone

Standard

SAEJ20R3

Colour



[View Product Online](#)

Hoses UK

Unit 5 Holme Bank Mills
Station Road
Mirfield
West Yorkshire
WF14 8NA

Contact:

01924 496111
web@hosesuk.co.uk
hosesuk.co.uk

Hose Distribution. Simplified.