



## Polyurethane PU Ducting

| Inside Diameter | Outside Diameter | Wall Thickness | Negative Pressure | Bending Radius | Coil Weight | Coil Length |
|-----------------|------------------|----------------|-------------------|----------------|-------------|-------------|
| 50mm            | 60mm             | 0.4mm          | -0.20 Bar         | 32mm           | 7.7kg       | 20 Metre    |
| 65mm            | 75mm             | 0.4mm          | -0.17 Bar         | 55mm           | 9.8kg       | 20 Metre    |
| 80mm            | 90mm             | 0.4mm          | -0.16 Bar         | 65mm           | 14.2kg      | 20 Metre    |
| 100mm           | 110mm            | 0.4mm          | -0.13 Bar         | 85mm           | 7kg         | 10 Metre    |
| 125mm           | 135mm            | 0.4mm          | -0.01 Bar         | 105mm          | 8.9kg       | 10 Metre    |
| 150mm           | 160mm            | 0.4mm          | -0.08 Bar         | 125mm          | 11.5kg      | 10 Metre    |
| 200mm           | 210mm            | 0.4mm          | -0.04 Bar         | 165mm          | 13.5kg      | 10 Metre    |

**SKU - PUD**

**Operating Temperature**

-40°C to +90°C

**Peak Temperature**

+125°C

**Inner Layer Material**

Semi-Transparent  
Polyurethane (PU)

**Reinforcement**

Copper Plated Left Hand  
Spiral Steel Wire, Anti Static

**Outer Layer Material**

**Standard**

TRBS2153

**Colour**



**[View Product Online](#)**

**Hoses UK**

Unit 5 Holme Bank Mills  
Station Road  
Mirfield  
West Yorkshire  
WF14 8NA

**Contact:**

01924 496111  
[web@hosesuk.co.uk](mailto:web@hosesuk.co.uk)  
[hosesuk.co.uk](http://hosesuk.co.uk)

**Hose Distribution. Simplified.**