



SKU - PUDJK - Black
PUDJW - Clear

Operating Temperature
-20°C to +105°C

Peak Temperature
+110°C

Inner Layer Material
Acrylonitrile Butadiene Styrene
(ABS)

Reinforcement

Outer Layer Material
Acrylonitrile Butadiene Styrene
(ABS)

Standard
BS EN ISO 3994-2001

Colour
☒ ☐

[View Product Online](#)

Hoses UK
Unit 5 Holme Bank Mills
Station Road
Mirfield
West Yorkshire
WF14 8NA

Contact:
01924 496111
web@hosesuk.co.uk
hosesuk.co.uk

HOSESUK
WHOLESALE

Polyurethane Ducting ABS Connector

Inside Diameter	Outside Diameter	Wall Thickness	Working Pressure	Bursting Pressure	Weight	Length
45mm	50mm	2.5mm	0 Bar	0 Bar	49g	100mm
60mm	65mm	2.5mm	0 Bar	0 Bar	53g	100mm
75mm	80mm	2.5mm	0 Bar	0 Bar	65g	100mm
95mm	100mm	2.5mm	0 Bar	0 Bar	105g	100mm
120mm	125mm	2.5mm	0 Bar	0 Bar	126g	100mm
145mm	150mm	2.5mm	0 Bar	0 Bar	145g	100mm

Hose Distribution. Simplified.