



Rubber Marine Hose

Inside Diameter	Outside Diameter	Wall Thickness	Working Pressure	Bursting Pressure	Bending Radius	Coil Weight	Coil Length
5mm	12mm	3.5mm	10 Bar	30 Bar	72mm	17kg	100 Metre
6mm	13mm	3.5mm	10 Bar	30 Bar	78mm	18kg	100 Metre
8mm	15mm	3.5mm	10 Bar	30 Bar	90mm	20kg	100 Metre
10mm	17mm	3.5mm	10 Bar	30 Bar	102mm	24.5kg	100 Metre
13mm	21mm	4mm	10 Bar	30 Bar	126mm	32kg	100 Metre
16mm	25mm	4.5mm	10 Bar	30 Bar	150mm	10kg	50 Metre
19mm	28mm	4.5mm	10 Bar	30 Bar	168mm	25kg	50 Metre
25mm	36mm	5.5mm	5 Bar	15 Bar	216mm	14kg	20 Metre
32mm	42mm	5mm	5 Bar	15 Bar	252mm	17kg	20 Metre
38mm	50mm	6mm	5 Bar	15 Bar	300mm	20kg	20 Metre
51mm	63mm	6mm	5 Bar	15 Bar	378mm	24kg	20 Metre

SKU - RMH

Operating Temperature

-40°C to +100°C

Peak Temperature

+120°C

Inner Layer Material

Black Smooth Nitrile Rubber

Reinforcement

High Strength Polyester Braids

Outer Layer Material

Black Smooth Synthetic Nitrile Blend

Standard

BS EN ISO 7840

Colour



[View Product Online](#)

Hoses UK

Unit 5 Holme Bank Mills
Station Road
Mirfield
West Yorkshire
WF14 8NA

Contact:

01924 496111
web@hosesuk.co.uk
hosesuk.co.uk

Hose Distribution. Simplified.