



Rubber Multi Purpose Hose

Inside Diameter	Outside Diameter	Wall Thickness	Working Pressure	Bursting Pressure	Bending Radius	Coil Weight	Coil Length
5mm	12mm	3.5mm	20 Bar	60 Bar	72mm	17kg	100 Metre
6mm	13mm	3.5mm	20 Bar	60 Bar	78mm	18kg	100 Metre
8mm	15mm	3.5mm	20 Bar	60 Bar	90mm	20kg	100 Metre
10mm	17mm	3.5mm	20 Bar	60 Bar	102mm	24.5kg	100 Metre
13mm	21mm	4mm	20 Bar	60 Bar	126mm	32kg	100 Metre
16mm	25mm	4.5mm	20 Bar	60 Bar	150mm	20kg	50 Metre
19mm	29mm	4.5mm	20 Bar	60 Bar	168mm	25kg	50 Metre
22mm	32mm	5mm	20 Bar	60 Bar	192mm	30kg	50 Metre
25mm	36mm	5.5mm	20 Bar	60 Bar	216mm	35kg	50 Metre

SKU - RPH

Operating Temperature

-20°C to +100°C

Peak Temperature

+120°C

Inner Layer Material

Black Smooth Oil Resistant
Synthetic Rubber

Reinforcement

High Tensile Fabric Layers

Outer Layer Material

Black Smooth Oil Resistant
NBR Rubber

Standard

ISO 73379

Colour



[View Product Online](#)

Hoses UK

Unit 5 Holme Bank Mills
Station Road
Mirfield
West Yorkshire
WF14 8NA

Contact:

01924 496111

web@hosesuk.co.uk

hosesuk.co.uk

Hose Distribution. Simplified.