



Silicone Hump Hose

Inside Diameter	Outside Diameter	Wall Thickness	Working Pressure	Bursting Pressure	Number Of Ply	Length
25mm	34mm	4.5mm	5.5 Bar	16 Bar	3	102mm
32mm	41mm	4.5mm	5.17 Bar	15.5 Bar	3	102mm
38mm	47mm	4.5mm	5 Bar	15 Bar	3	102mm
45mm	54mm	4.5mm	4.67 Bar	14 Bar	3	102mm
51mm	62mm	5.5mm	4.5 Bar	13.5 Bar	4	102mm
57mm	68mm	5.5mm	4.33 Bar	13 Bar	4	102mm
60mm	71mm	5.5mm	4.17 Bar	12.5 Bar	4	102mm
63mm	74mm	5.5mm	4 Bar	12 Bar	4	102mm
70mm	81mm	5.5mm	3.6 Bar	11 Bar	4	102mm
76mm	87mm	5.5mm	3.5 Bar	10.5 Bar	4	102mm
80mm	91mm	5.5mm	3.33 Bar	10 Bar	4	102mm
90mm	101mm	5.5mm	3.17 Bar	9.50 Bar	4	102mm
102mm	113mm	5.5mm	2.83 Bar	8.5 Bar	4	102mm

SKU - SHU

Operating Temperature
-50°C to +250°C

Peak Temperature
+250°C

Inner Layer Material
Smooth Extruded Silicone Compound

Reinforcement
Polyester Braids

Outer Layer Material
Silicone

Standard
SAEJ20R3

Colour



[View Product Online](#)

Hoses UK

Unit 5 Holme Bank Mills
Station Road
Mirfield
West Yorkshire
WF14 8NA

Contact:

01924 496111
web@hosesuk.co.uk
hosesuk.co.uk

Hose Distribution. Simplified.